



Pulse Amplifier Tetrodes-Glass Envelope, Forced-air Cooled

Pulse output power	Tube Type	Anode dissipation max. (W)	Anode voltage max. D.C. (KV)	Pulse anode current max. (A)	Duty cycle	Filament		Base	Type tube replaced
						Voltage (V)	Current (A)		
3.100 kW	338	1.000 W	42 kV	90 A	0,0010	25,0 V	13,5 A		
2.700 kW	TM - 86F	1.000 W	40 kV	80 A	0,0010	25,0 V	13,5 A		
2.400 kW	TM - 2F	900 W	32 kV	110 A	0,0015	25,0 V	17,5 A		
1.100 kW	TM - 90	140 W	33 kV	45 A	0,0010	25,0 V	7,2 A		
330 kW	TM - 13/4PR60C	60 W	20 kV	18 A	0,0010	26,0 V	2,2 A	GB787-74 J4-3A	C1149B
330 kW	TM - 12/C1149	60 W	20 kV	18 A	0,0010	26,0 V	2,2 A	GB787-74 J4-3A	CV6131
250 kW	TM - 85	65 W	20 kV	18 A	0,0010	25,0 V	2,0 A	GB787-74 J4-3A	
205 kW	TM - 15/C1166	60 W	18 kV	15 A	0,0010	6,3 V	9,0 A	IEC 67-1-21c	CV10404
64 kW	4PR400A	400 W	20 kV	4 A	0,0550	5,0 V	14,5 A	IEC 67-1-21b	5F23P

